



RS232 to RS485 CONVERTER

The versatile RS-232 Async Multidrop Line Driver is an RS-232 to RS-485 interface converter that operates much like a short haul modem. You can transmit data over much longer distances than is normally possible. You can also multidrop applications, as well as point-to-point. In fact, you can daisy-chain these drivers and run up to 32 devices on a wire pair. And at 64 Kbps, your async data moves quickly.

??RS-232 to RS-485 conversion using 2-wire half duplex.

??Multidrop up to 32 devices.

??Drivers are enabled by data—no RTS control necessary.

??Built in surge and lightning protection on RS-485 lines.

??RS-485 lines can be up to 2000 metres long.

??Can be powered from DC or AC power supplies of 8 to 25 volts.

SPECIFICATIONS

Model: ACC6500

Protocol: Asynchronous

Maximum Distance: 2000 metres

Operation: 2-wire half duplex, point-to-point or multidrop

Interface: RS-232/V.24 and RS-485

Connectors: DB9 female RS-232 & RS-485;
4-screw terminal block RS-485;
3-screw terminal block power.

Power: 8-25 volts AC or DC @ 50mA

Size: 75 mm x 50 mm

CONNECTIONS

DB9 Female Connector

pin 1 = RS-485 data -
pin 2 = RS-232 data in
pin 3 = RS-232 data out
pin 4 = no connect
pin 5 = ground
pin 6 = RS485 data +
pin 7 = link to pin 8
pin 8 = link to pin 7
pin 9 = power in (+8 to +25 volts DC)

TB1 Terminal Block

+RS485 =RS-485 data +
+RS485 = RS-485 data +
-RS485 = RS-485 data -
-RS485 = RS-485 data -

TB2 Terminal Block

EARTH = connect to earth
+AC = +volts DC or AC
-AC = -volts DC or AC

Malloch Digital Design Pty Ltd

PO Box 790

Fyshwick ACT 2609

Tel: (02)6162-2812 Fax: (02)6161-2812 support@mallochdigital.com